

POWERPLUS[®] LIGHT

HIGH QUALITY TOOLS



LED lights







our
NEW
RANGE



our
**NEW
RANGE**

Nominal lifetime
>50.000h



	POWLI220	POWLI221	POWLI226	POWLI230	POWLI231	POWLI234
Power	10W	10W + sensor	10W rechargeable	20W	20W + sensor	20W
LED type	Epistar SMD	Epistar SMD	Epistar SMD	Epistar SMD	Epistar SMD	Epistar SMD
Protection degree	IP65	IP44	IP44	IP65	IP44	IP65
Colour temperature	6500K	6500K	6500K	6500K	6500K	6500K
Lumen	720 lm	720 lm	700 lm	1440 lm	1440 lm	2000 lm
Working time	-	-	2.5h	-	-	-
Charging time	-	-	3h	-	-	-
Battery	-	-	7.4V Li-Ion - 2600mAh	-	-	-
Cable	-	-	-	-	-	1.5m
Beam angle	120°	120°	120°	120°	120°	120°
Features	-	-	Head turns 120°	-	-	Head turns 120°
Barcode	 5 400338 054471 >	 5 400338 054501 >	 5 400338 069369 >	 5 400338 054518 >	 5 400338 054525 >	 5 400338 066788 >

Nominal lifetime
>30.000h







 **BEST DEAL**



Power	
LED type	SMD
Protection degree	IP65
Colour temperature	6500K
Lumen	750 lm
Working time	-
Charging time	-
Connection cable	0.30m
Beam angle	110°
Features	
Barcode	

POWLI20110	POWLI20210	POWLI20310	POWLI20510
10W	20W	30W	50W
SMD	SMD	SMD	SMD
IP65	IP65	IP65	IP65
6500K	6500K	6500K	6500K
750 lm	1500 lm	2250 lm	3750 lm
-	-	-	-
-	-	-	-
0.30m	0.30m	0.30m	0.30m
110°	110°	110°	110°
BEST DEAL	BEST DEAL	BEST DEAL	BEST DEAL
 5 400338 072192 >	 5 400338 072208 >	 5 400338 072215 >	 5 400338 072222 >



POWLI235	POWLI236	POWLI240	POWLI241	POWLI260	POWLI261
20W + tripod	20W rechargeable	30W	30W + sensor	50W	50W + sensor
Epistar SMD	Epistar SMD	Epistar SMD	Epistar SMD	Epistar SMD	Epistar SMD
IP65	IP44	IP65	IP44	IP65	IP44
6500K	6500K	6500K	6500K	6500K	6500K
1400 lm	1800 / 900 / 450 lm	2160 lm	2160 lm	3600 lm	3600 lm
-	2.5h / 3.5h / 6h	-	-	-	-
-	3.5h	-	-	-	-
-	7.4V Li-Ion - 5200mAh	-	-	-	-
2.5m	-	-	-	-	-
120°	120°	120°	120°	120°	120°
Head turns 120°	Head turns 120°	-	-	-	-
 5 400338 066795 >	 5 400338 066818 >	 5 400338 054532 >	 5 400338 054570 >	 5 400338 057601 >	 5 400338 057618 >

Nominal lifetime
>30.000h



	POWLI20100	POWLI20200	POWLI20201	POWLI20300	POWLI20301
Power	10W	20W	20W + sensor	30W	30W + sensor
LED type	SMD	SMD	SMD	SMD	SMD
Protection degree	IP65	IP65	IP65	IP65	IP65
Colour temperature	6500K	6500K	6500K	6500K	6500K
Lumen	650 lm	1500 lm	1500 lm	2250 lm	2250 lm
Sensor range	-	-	120°	-	120°
Sensor distance	-	-	1 - 6m	-	1 - 6m
Sensor delay time	-	-	3 - 300 sec	-	3 - 300 sec
Sensor lux	-	-	10 - 1000 lux	-	10 - 1000 lux
Connection cable	0.30m	0.30m	0.30m	0.30m	0.30m
Beam angle	100°	100°	100°	100°	100°
Features	-	-	-	-	-
Barcode	5 400338 072239 >	5 400338 072246 >	5 400338 072253 >	5 400338 072260 >	5 400338 072277 >



	POWLI20500	POWLI20501
Power	50W	50W + sensor
LED type	SMD	SMD
Protection degree	IP65	IP65
Colour temperature	6500K	6500K
Lumen	3750 lm	3750 lm
Sensor range	-	120°
Sensor distance	-	1 - 6m
Sensor delay time	-	3 - 300 sec
Sensor lux	-	10 - 1000 lux
Connection cable	0.30m	0.30m
Beam angle	100°	100°
Features	-	-
Barcode	5 400338 072284 >	5 400338 072291 >



	POWLI23129	POWLI23229
Power	10W	20W
LED type	Epistar SMD	Epistar SMD
Protection degree	IP65	IP65
Colour temperature	3000K	3000K
Lumen	650 lm	1300 lm
Sensor range	-	-
Sensor distance	-	-
Sensor delay time	-	-
Sensor lux	-	-
Connection cable	0.30m	0.30m
Beam angle	110°	110°
Features	360° rotatable + 120° tiltable	360° rotatable + 120° tiltable
Barcode	5 400338 072307 >	5 400338 072314 >



designed & marketed by
VARO

VARO - VIC. VAN ROMPUY nv
JOSEPH VAN INSTRAAT 9
2500 LIER - BELGIUM
WWW.VARO.COM

OFFICES:
IBERICA BRICOLAGE S.L. - ESPAÑA
ASIA PACIFIC HONG KONG Ltd / SHANGHAI PRC
AUSTRALIA Pty Ltd / GERMANY GmbH

ARTFOL16050063

