



**HIGH POWER LED**

**SURFACE MOUNTED LED**

**30W**

**50.000h**  
NOMINAL LIFETIME

**2160 LUMEN**

**6500 KELVIN**

**220-240V~ 50Hz**



This nicely designed LED floodlight can be used indoor and outdoor. Its firm aluminium housing and protection level of IP65 protects it against dust and water, what makes it perfect for use at the jobsite, in the garden, studio and workshop. It emits 2160 lumen with 30W of electricity which makes it a great energy saving floodlight.

The POWLI240 has a high-quality surface mounted LED light that produces a natural daylight colour temperature of 6500K. On top of that, the floodlight has a service life of over 50.000 operating hours. The floodlight is easy to install and can be pointed at different angles thanks to its adjustable bracket.



TECHNICAL SPECIFICATIONS <b>POWLI240</b>		Features	Box content	Symbols
Power	220-240V~ 50Hz	<ul style="list-style-type: none"> <li>Epistar surface mounted LED</li> <li>Adjustable bracket</li> </ul>	1x LED floodlight	<b>CHEMICAL SAFETY</b> ✓ <b>Intertek</b> <b>GS</b> <b>CE</b>
Lumen	2160Lm		1x manual	
Nominal lifetime	50.000h			
Colour temperature	6500K			
Material	Aluminium housing			
Protection degree	IP65			